

REMARKS

This Preliminary Amendment cancels the original claims, without prejudice, in the underlying PCT Application No. PCT/DE03/01057. The Preliminary Amendment also adds new claims 17-34. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/01057 includes an International Search Report, dated October 30, 2003, a copy of which is submitted herewith.

Applicant asserts that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

Dated: 12/9/04

KENYON & KENYON
By: Richard L. Mayer (Reg. No. 22,490)
Richard L. Mayer
(Reg. No. 22,490)

One Broadway
New York, NY 10004
(212) 425-7200

[10191/3901]

SWITCHING REGULATOR, STEP-DOWN TRANSFORMER
IN PARTICULAR, AND SWITCHING REGULATION METHOD~~Background Information~~ Field Of The Invention

The present invention relates to a switching regulator, a step-down transformer in particular, and a switching regulation method.

5 Background Information

Switching regulators (SR), such as buck converters or step-down converters, are used in many applications, for voltage matching and voltage reduction in particular, in switched-mode power supplies, for example.

- 10 In direct voltage supply circuits (power supply units) voltage is generally regulated by switching regulators via a timing voltage which is applied to the control terminal of a power transistor. In the simplest case, a timing frequency is derived by the regulator from the direct voltage (controlled variable) to be regulated according to the deviation from the reference variable (system deviation) and this timing frequency times the power transistor and thus
15 provides the regulated output direct voltage, after low-pass filtering in particular.

The open loop gain of a switching regulator results essentially from a gain v_R of a control amplifier, gain V_{PWM} of a pulse-width modulator (PWM), ratio k_{ist} of an actual voltage divider of the output voltage in the feedback path, and the gain or damping H_{TPLC} of an LC
20 low-pass filter at the output of a power amplifier of the switching regulator: ($V = k_{actual} \times v_R \times V_{PWM} \times H_{TPLC}$).

Gain factor V_{PWM} of the pulse-width modulator results from the quotient between a battery voltage U_{BAT} (input signal) and a delta voltage U_{osc} which is supplied to the pulse-width
25 modulator ($V_{PWM} = U_{BAT}/U_{osc}$), delta voltage U_{osc} being $1.25 V_{SS}$, for example.

Due to the great fluctuation range of battery voltage U_{BAT} , of approximately 6 V to 40 V, and possibly even 60 V, which must be taken into account, gain factor V_{PWM} of pulse-width modulator (PWM) has a relatively large dynamic range. As a result, the total gain varies by a
30 factor of 10 (20 dB) due to the battery voltage variation range alone, which may result in

stability problems of the overall control circuit, or in control and accuracy losses in the case of a reserve established on the basis of the maximum gain.

Changes in the battery voltage, in particular sudden changes, are identified and subsequently adjusted in the feedback path of the control circuit of a switching regulator only with a relatively long delay time, which results in dynamic harmonics in the output voltage.

Relevant for the delay is the LC low-pass filter (H_{TPLC}) having a cut-off frequency f_{gTP} of:
$$f_{gTP} = (1/2\pi) \times (1/(LC))^{0.5}.$$

A typical method for circumventing the above-named problems is presented in M.R. BORGHI Smart Power ICs, Springer Verlag 1996. The amplitude of delta voltage U_{osc} supplied to the pulse-width modulator is regulated as a function of the battery voltage $U_{osc} = f(U_{BAT})$, delta voltage U_{osc} being in the range between 200 mV and 2 V, for example. One disadvantage in the case of relatively small amplitudes of delta voltage U_{osc} in a timed system results due to the resolution inaccuracy, which is critical. In addition, amplitude feedforward compensation is relatively complicated to implement.

Another typical method for circumventing the above-described problems is a pre-distortion of delta voltage U_{osc} , the oscillator voltage supplied to the pulse-width modulator being only quasi-delta shaped, and a linear section in the area of the tip of the delta having an exponential area where no feedforward effect is achieved, since the oscillator does not change its voltage amplitude, in particular not as a function of battery voltage U_{BAT} , and thus no direct compensation regulation occurs (see also MULLER RS, KAMINS TI (1986) Devices For Electronics Integrated Circuit, John Wiley & Sons).

Summary Of The Invention

An object of the present invention is to provide a switching regulator, in particular having feedforward compensation, and also a switching regulation method having a gain which is essentially independent of an input signal.

Advantages of the Invention

~~This object is achieved according to the present invention by the switching regulator as recited in Claim 1 and the switching regulation method as recited in Claim 12.~~

The present invention is based on the fact that gain v_R of a control amplifier is approximately proportional to the battery voltage.

The object of the present invention as recited in the preamble is achieved in particular by the fact that a compensation device controls gain factor v_R as a function of an input voltage, in particular a fluctuating input voltage (U_{BAT} , for example), in such a way that the overall gain of the switching regulator remains essentially constant over battery voltage U_{BAT} .

~~Advantageous refinements of and improvements on the respective objects of the main claims are presented in the subclaims.~~

According to an advantageous refinement, an amplifier device has a complex grounded resistor, in particular for adjusting a primary gain and/or frequency compensation.

According to another preferred refinement, a filtering device has a low-pass filter, in particular having an inductance and a capacitance and a diode connected in parallel thereto.

According to another preferred embodiment, the oscillator signal supplied to the pulse-width modulating device has a delta oscillator voltage.

According to another preferred refinement, a switching device has a transistor, a MOSFET in particular.

Brief Description Of The Drawing

~~An exemplary embodiment of the present invention is depicted in the drawing and elucidated in detail in the description that follows.~~

The Figure 1—shows the block diagram of a switching regulator, having feedforward compensation in particular, to elucidate an embodiment according to the present invention.

Detailed Description of the Exemplary Embodiments

~~Figure 1 shows the block diagram of a switching regulator, having feedforward compensation in particular, to elucidate an embodiment according to the present invention.~~

The Figure shows the block diagram of a switching regulator, having feedforward compensation in particular, to elucidate an embodiment according to the present invention.

~~In Figure 1,~~*The Figure*, an input signal 1, a battery voltage U_{BAT} in particular, is supplied to a compensation device 2, a feedforward compensation module (FFK) in particular, which generates a compensation signal 3, a compensation current I_{FFK} in particular, as a function of the amplitude of input signal 1.

An amplifier device 7, a control amplifier R_V or transconductance amplifier in particular, receives compensation signal 3 and modifies gain factor 6 v_R of amplifier device 7 according to compensation signal 3. A complex resistor 8 is connected to amplifier device 7 and is essentially used for adjusting the primary gain of amplifier device 7 and/or the frequency compensation. A reference signal 4, a reference voltage U_{REF} in particular, and an actual value signal 5, an actual voltage U_{actual} in particular, are also supplied to amplifier device 7 to generate an amplifier signal 23.

An oscillator signal 9, a delta oscillator voltage U_{osc} in particular, having any desired, essentially constant, amplitude is also supplied, as is amplifier signal 23, to a pulse-width modulating device 11, a pulse-width modulator (PWM) in particular, which generates a pulse-width modulated signal 22 amplified by a gain v_{PWM} , which is supplied to an additional amplifier device 12 having gain v_p . A switching signal 21 is generated in amplifier device 12, which is essentially used as a power adapter for actuating a switching device 13.

Switching device 13, a MOSFET power amplifier in particular, switches through input signal 1 as a function of switching signal 21 to a filtering device 14 and as a result generates a pulsed signal 24, which is smoothed in filtering device 14, which has a low-pass filter in particular having a serial inductance 15 and a grounded capacitance 17 connected downstream from inductance 15.

A freewheeling diode 16, which is used for protecting filtering device 14 against voltage surges, among other things, is connected to ground in parallel to filtering device 14. Pulsed signal 24 is smoothed in filtering device 14 to yield output signal 18, a voltage in particular, which is supplied to amplifier device 7 (actual value signal 5) via a resistor network 19, a voltage divider 19 in particular having gain or division k_{ist} , and a feedback path 20.

Gain v_R or transconductance s_R of control amplifier 7 is corrected using battery voltage U_{BAT} (input signal 1) in such a way that the product $v_1 = (U_{BAT}/U_{osc}) \times v_R$ remains constant over the battery voltage.

Delta oscillator voltage U_{osc} may be selected arbitrarily, e.g., $U_{osc} = 1.25 \text{ V}$. The loop gain in the control circuit of a buck converter, which in first approximation is independent of the battery voltage according to the present invention, represents an implementation of a feedforward compensation, i.e., the control amplifier or pulse-width modulator responds to a sudden change in the battery voltage immediately, without delay of the output-side low-pass filter.

The implementation of such a switching regulator using feedforward compensation is inexpensive and requires little space.

For gain v_R of control amplifier RV, the following applies:

$$v_R = Z \times [1/(R \times k \times U_{BAT})],$$

where Z represents the complex resistance of a selectable external resistor, having an ohmic

5 and/or capacitive resistance in particular. The product of transconductance S_R and complex resistance Z is also equal to gain v_R of control amplifier RV, transconductance S_R being compensation current I_{FFK} divided by temperature voltage U_T , and compensation current I_{FFK} being generatable from a ring-type current source and satisfying the equation $I_{FFK} = U_c / (R \times k \times U_{BAT})$, R being the $Tk0$ resistance of the ring-type current source, and k being a factor for
10 adjusting gain v_R . By combining the above equations and equation $V_{PWM} = U_{BAT}/U_{osc}$, the product of the two gains V_R and $V_{PWM} = v_1$ becomes $v_1 = Z / (R \times k \times U_{osc})$, which in first approximation is independent of the battery voltage and in the event of battery voltage surges corrects the gain dynamically, without delay time of the output low-pass filter, so that harmonics in output voltage V_{out} are prevented.

15 Although the present invention was described above with reference to a preferred exemplary embodiment, it is not limited thereto, but may be modified in many ways.

Although in the example above the compensation device emits a current signal for controlling
20 the gain factor of the amplifier device, another signal form (voltage signal, optical signal, etc.) is also conceivable here or for the other mentioned signals. A different oscillator output signal form is also conceivable, as well as a modified filtering device or the omission of the additional amplifier device having gain factor v_p .

25 The present invention is also not limited to the above-mentioned applications.

Abstract Of The Disclosure

5 A switching regulator, a step-down transformer in particular, is described, which has a
switching device ~~(13)~~ for generating a pulsed signal ~~(24)~~ from an input signal ~~(1)~~ as a
function of a switching signal ~~(21)~~; a filtering device ~~(14)~~ for filtering the pulsed signal ~~(24)~~
10 and for outputting a smoothed output signal ~~(18)~~; a controllable amplifier device ~~(7, 11, 12)~~
for generating the switching signal ~~(21)~~ from a reference signal ~~(4)~~ and an actual value signal
~~(5)~~ obtained from the output signal ~~(18)~~ via a feedback device ~~(19, 20)~~ as a function of a
compensation signal ~~(3)~~; and a compensation-signal generating device (2) for generating the
15 compensation signal (3) from the input signal (1). A switching regulation method is also
described.

Figure 1